

SPECIFICATIONS: MSE-24CRN2



MSE-24CRN2

Capacity			
Cooling		Btu/h	23000
		kW	6.7
Electrical Parts			
Voltage, Frequency, Phase		V~,Hz,Ph	220-240, 50, 1
Power Input	Cooling	w	2680
Operating Current	Cooling	w	12.5
Performance			
EER		Btu/W.h,	8.6,2.51
COP		W/W	-
Energy Rate			E
Air Flow Volume	Indoor	m3/h	1020
Noise Level	Indoor(Hi/Med/Lo)	dB(A)	45/42/39
	Outdoor	dB(A)	55
Net Dimension & Weight			
Indoor unit	WxHxD	mm	845x695x335
Outdoor unit	WxHxD	mm	1080x330x225
Net Weight	Indoor/Outdoor	kg	17/59
Packing Dimension & Gross Weight			
Indoor unit	WxHxD	mm	970x770x395
Outdoor unit	WxHxD	mm	1165x445x320
Gross Weight	Indoor/Outdoor	kg	21/63
Piping Connection			
Liquid Side		mm(inch)	Ø9.53(3/8")
Gas Side		mm(inch)	Ø16.0(5/8")
Applicable Area			
		m2	45-56

FEATURES: MSE-24CRN2



Auto Restart Function

When the power is off then on, the unit automatically restores the previous function setting.



Sleep Mode

This function enables the unit to automatically increase (cooling) 1° C per hour for the first 2 hours, then hold steady for the next 5 hrs, after that the unit will stop operation. It can maintain the most comfortable temperature and save energy.



Turbo Mode

This function enables the unit to reach the preset temperature in the shortest time.



Two Speed Fan Motors (21,000 Btu/h Models only)

With a two-speed fan motor, the outdoor unit can operate powerfully at high speed or can be adjusted to quiet and low speed operation at night.