

Specifications

Inverter Hi-wall Single Split Type



System

Cooling Only (R-410a)

Nominal Rating, Hp		1
Model	(Indoor Unit)	42CVSR010-703
	(Outdoor Unit)	38CVSR010-703
Power Supply	(V/ph/Hz)	220-240/1/50
Cooling Capacity	(kW)	2.50(1.10~2.90)
COP		3.25(4.23~3.01)
Power Consumption (Cooling)	(kW)	0.77(0.26~0.96)
Operating Current (Cooling)	(A)	3.53(1.61~4.42)
Indoor Unit		
Dimension (HxWxD)	(mm)	250x740x195
Net weight	(kg)	8
Humidity capacity	(l/h)	1.5
Airflow Volume	(m3/h)	522
Fan Motor Output	(W)	20
Operating Noise (H/M/L), (H/M+/M/L+/L)	(dB)	39/36/34/32/30
Sound power level (High)	(dBA)	52
Outdoor Unit		
Dimension (HxWxD)	(mm)	530x660x240
Net weight	(kg)	29
Compressor Output	(W)	750
Fan Motor Output	(W)	20
Operating Noise	(dB)	48
Sound power level (High)	(dBA)	61
Pipe Size		
Liquide Side	(mm/inch)	6.35(1/4")
Gas Side	(mm/inch)	9.52(3/8")
Coupler Style Flare	Flare	Flare
Drain (Inside Dia. Mm)	mm)	16.3
Max. Piping Length	(m)	10
Chargeless Length	(m)	10
Max. Piping Height	(m)	8
Usable Outdoor Temp	(Cooling, °C)	15-43
Air filter (Accessory)		Nano Photo Copper Zinc 1 pc Nano Silver Ginseng 1 pc





